

INDUSTRIAL WEIGHING SOLUTION™

# HD SERIES

## High Resolution Platform Scale

HD is an advanced platform scale with high resolution and various functions. It is suitable for use in parts production, paint industry and logistics center. It can be connected to various printers for data collection and offer great mobility with its rechargeable battery.



High-Resolution Weighing (1/15,000)

Counting & Percent mode Support

Easy operation with 8 function Keys

Rechargeable Battery

Counting & Percent mode Supported



Easy operation with 8 function keys



Rechargeable Battery



**CAS**  
www.casscale.co.nz

# HD SERIES

## High Resolution Platform Scale



### FEATURE

- Counting & Percent mode Supported  
1 / 15,000 high-resolution and a more accurate counting, percentage modes are supported.



- Check-Weighing function  
(HI/OK/LO is separately displayed)  
Weight and Counting, percent mode are available.



- Easy operation with 8 function keys  
Various Function Keys offer easy operation.

Key	Descriptions	Key	Descriptions	Key	Descriptions
	Used to set the zero point to 0.00. Used as an ESC key in Setup Mode.		Used as an ENTER key.		PRINT key. Used to have number down.
	Used to enter a tare weight and Used to cancel a tare weight.		Used to calculate a unit weight of a sample. Used to enter next digit.		Used to turn ON or OFF the power.
	Used to convert the mode as below. (kg) > (g) > (N) > (OZ) > (LBS) > (COUNT LIMIT ON/OFF) > (COUNT LIMIT ON/OFF) > (kg)		Used to have number up.		

- Rechargeable Battery  
The rechargeable battery increases portability and allows HDI to be used in environments where little or no power is available.  
(Charging time : 12Hour / Battery life: 80Hour)



### SPECIFICATION

MODEL		HD	
kg Version	Capacity	150 kg	300 kg
	Readability(e=d)	10g	20g
	Resolution	1/3,000 ~ 1/15,000	
Internal Resolution		1/300,000	
Display Type		LCD	
Display Indicators		Stability, Center of Zero, Gross, Net, Battery status, Hi-Ok-Lo, Units	
Hi-Lo Check Indicators		Display with Alert beeper	
Weight Units		kg	
Zero Range		±2%	
Tare Range		Full Capacity by Subtraction	
Operation Temperature		0°C ~ 40°C	
Humidity Range		≤90% relative humidity, non-condensing	
Power		AC Adaptor 12V/800mA Internal rechargeable sealed acid battery	
Battery Life		80 hours continuous use with 12 hour recharge time	
Calibration		Automatic external with kg mass, factory calibration recovery	
Safe Overload Capacity		120% of capacity	
Dimension		400(W) X 630(D) X 750(H) mm	
Pan Size		400(W) X 500(D) mm	
Product Weight		15 kg	

### APPLICATION

Parts Production  
Paint Processing  
Industrial production  
Logistics Center



CAS NEW ZEALAND LTD,  
UNIT 1, 4 FREEMAN WAY  
MANUKAU CITY 2104  
TEL 09 263 7225

Specifications are subject to change without notice improvement

