



More information on the website
radwag.com/en/info,w1,5BJ

PUE HX5.EX-4 Terminal



Functions



Labelling



Plus/Minus Control



Percent Weighing



Parts counting



Newton unit measurement



Statistics



GLP Procedures



Replaceable unit



ALIBI Memory

Datasheet

Metrological parameters	
Maximum quantity of verification units	6000 e
OIML Class	III
Maximum quantity of divisions from converter	100 000
Maximum increase of signal	19,5 mV
Minimum volatge per verification unit	0,4 μ V
Minimum load cell impedance	80 Ω
Maximum load cell impedance	1200 Ω

Metrological parameters	
Connection of load cells	4 or 6 wires + shield
Physical parameters	
Display	5" graphic colour
Device dimensions	329×231×120 mm
Packaging dimensions	640×310×220 mm
Net weight	7,8
Gross weight	8,8
Protection class	IP 66 / IP 68
ATEX Certification	II 2G Ex ib IIC T4 Gb (gases) II 2D Ex ib IIIC T60°C Db (dusts)
Working in zones	1, 2 (gases); 21, 22 (dusts)
Communication interface	
Communication interface	2×RS232, RS485, 4 OUT
Environmental conditions	
Operating temperature	-10 ÷ +40 °C
Construction	
Housing	stainless steel



Compatible with

Stainless Steel HRP EX.H Platforms
Communication modules
HRP EX Platforms

Power Adapters
Communication Modules

Software

RAD-KEY
Label Editor R02
R-LAB
E2R System

LabVIEW Driver
Alibi Reader
RADWAG Development Studio
R.Barcode